

TARGA PS6000

Awning for conservatories with motor drive. Fabric cover. Retraction and extension of the awning with tubular AC motor 230V/50 Hz with friction brake and electronic end stop. Thermal protection. Protection class IP44 (splash water), with 150 cm 4-pole connection cable. Box: Extruded aluminium profile, in one piece, rounded execution, as a construction support element with profile groove for the guide rail fixations. Side cap made of aluminium casting to hold the roller bearing or the motor bearing. Roller made of galvanised steel with groove for the cover. End rail made of extruded aluminium chamber profile with groove for the cover and the runner for the push and pull mechanism. With rolled in front rail, the box is completely closed. Guide rails made of extruded aluminium profiles, with grooves for the PVC glider, hollow chamber for the integrated gas-filled strut mechanism and stainless steel cable traction system for the transportation of the cover, and groove for the fixation support. The installation with a max. lateral overhang of 100 cm (left and right each) can be adjusted according to the frame work. Guide rail fixation supports made of aluminium casting. All visible screws in stainless steel.

Awnings with an extension of more than 300 cm are fitted with one guiding roller profile and more than 500 cm with two, including support sets for guiding roller profiles for the cover supports. Guiding roller profile is round extruded aluminium, guide rail fixings are cast aluminium alloy.

Options:

Electric drive

Remote control motor with an electronic limit switch: Tubular AC motor 230 V, 50 Hz or 120 V, 60 Hz (according to the country) with electromechanical brakes and electronic end stop. Integrated radio receiver, thermal protection, protection class IP44 (spray water), with 50 – 150 cm connection cable.

With 3 guides up to 700 cm total width / 700 cm extension (maximum 49 m)